

TPSh-M6M120SH1W

350W

Mechanical Specification

Cell Type	Mono Crystalline 166x83mm
Numbers of cells	120
Dimension	1755X1038X30mm
Weight	19.0kg
Front Glass	3.2 mm low iron tempered glass
Frame	Anodized aluminum
Junction Box	IP 67, with 3 bypass diodes
Connector	MC4 compatible
Output Cables	TÜV, 350mm 4.0mm ²

Module Series	TPSh-M6M120SH1W
Maximum Power at STC(Pmax) (W)	350
Short Circuit Current(Isc) (A)	11.15
Open Circuit Voltage(Voc) (V)	40.10
Maximum Power Current(Imp) (A)	10.42
Maximum Power Voltage(Vmpp) (V)	33.59
Module Efficiency	19.21%
Power Tolerance	0/+0%

Mechanical drawings (mm)

Nominal Operating Cell Temperature(NOCT)
Temperature Coefficient of Pmax()
Temperature Coefficient of Voc()
Temperature Coefficient of Isc()

China Headquarter

TEL: +86 755 86612689 / 86

FAX: +86 755 86611120

EMAIL: sales@topraysolar.com; info@topraysolar.com

ADDRESS: A-801 Future Plaza, Cuihuangbei Rd., Nanshan, Shenzhen, China

WWW: www.topraysolar.com; www.topraysolar.cn

